

Have sun!

On modules & mounting systems
**15 years
combination
warranty**



Extended performance warranty

Guaranteed higher long-term electricity profits owed to TOPCon technology.

Higher low light output

Even in low light conditions, for example at dusk and on cloudy days, increased power production is ensured.

Bifacial power generation

Up to 25% higher yield caused by double-sided active module, which absorbs sunlight with the front and the back.

Better cell protection

The front and back glass layer protects the cells from damaging and environmental impacts.

[Product datasheet](#)

IBC MonoSol 405 | 410 ES10-HC-N BF

High-quality double-glazed solar modules made of monocrystalline half-cut cells.

Online shop:
Find our products and further information here.




You also benefit from:

- a positive power tolerance (-0/+5W)
- increased mechanical stability (5400 Pa)
- a German guarantor
- 100% proved quality
- a 30-year performance warranty
- a 25-year product warranty



Have sun!



IBC MonoSol	405 ES10-HC-N BF	410 ES10-HC-N BF	Operating conditions	
Article number	2006200005	2006200003	Max. System Voltage (V)	1500
Electrical data (STC)²			Application Class	A
STC Power P _{max} (Wp)	405	410	Reverse Current I _r (A)	25
STC Nominal Voltage U _{mpp} (V)	31.3	31.5	Fuse protection from parallel strings	2
STC Nominal Current I _{mpp} (A)	12.95	13.02	Protection class	II (DIN EN 61140)
STC Open Circuit Voltage U _{oc} (V)	37.3	37.5	Fire protection	Class C (IEC 61730-ANSI/UL790)
STC Short Circuit Current I _{sc} (A)	13.75	13.82	Mechanical properties	
Module Efficiency (%)	20.67	20.92	Dimensions (L × W × H in mm)	1722 × 1134 × 30
Power Tolerance (W)	-0/+5	-0/+5	Weight (kg)	24,5
Electrical data (NMOT)			Max. Test load, Push/Pull (Pa)	5400/2400
NMOT (°C)	42	42	Max. Design load ² , Push/Pull (Pa)	3600/1600
800 W/m ² NMOT AM 1.5 Power P _{max} (Wp)	307	311	Front sheet (mm)	2.0 (low-iron photovoltaic glass and anti-reflective coating)
800 W/m ² NMOT AM 1.5 Nominal Voltage U _{mpp} (V)	29.4	29.6	Frame	anodized aluminium, sturdy hollow-chamber frame
800 W/m ² NMOT AM 1.5 Open Circuit Voltage U _{oc} (V)	35.7	35.8	Cells	12 × 9 mono-crystalline silicon cells
800 W/m ² NMOT AM 1.5 Short Circuit Current I _{sc} (A)	11.09	11.14	Connection type	EVO2
Relative Efficiency Reduction at 200 W/m ² (%)	≤ 5	≤ 5	Warranties and certification	
Temperature coefficient (linear)			Product warranty	25 years ¹
Tempcoeff I _{sc} (%/°C)	0.046	0.046	Performance warranty	30 years ¹
Tempcoeff U _{oc} (mV/°C)	-96.98	-97.50	Annual degradation	year 1 1,0% year 2-30 0,4%
Tempcoeff P _{mp} (%/°C)	-0.32	-0.32	Certification	IEC 61215, IEC 61730-1/-2, ISO 9001, ISO 14001, OHSAS 18001
			Packaging information	
			Number of modules per pallet	36
			Number of pallets per 40' container	26
			Dimensions incl. pallet (L × W × H in mm)	1764 x 1140 x 1254
			Gross weight incl. double pallet (kg)	918
			Stackability per pallet	2-fold

1) The linear power and product warranty are only valid for installations within Europe and Japan. The warranty requires installation according to the valid installation instructions. Standard test conditions: 1000 W/m² irradiation with a spectral distribution of AM 1.5 and a cell temperature of 25°C. 800 W/m², NOCT. Information according to EN 60904-3 (STC). All values according to DIN EN 50380. Errors and changes reserved. The precise conditions and content can be taken from the respectively valid version of the product and power warranty, which you can obtain from your IBC Premium Partner.

2) Loads according to IEC 61215-2:2016, max. design load

3) Measurement tolerances +/- 3% at STC: 1000 W/m², 25 +/- 2 °C, AM 1.5

Your Premium Partner